


FLEXIBLE SOLAR PANEL

YH400W-24M



ELECTRICAL DATA

Model Type	YH400W-24M
Peak Power(Pmax)	400
Maximum Power Voltage(Vmp)	29.05V
Maximum Power Current(Imp)	13.77A
Open Circuit Voltage(Voc)	34.18V
Short Circuit Current(Isc)	14.73A
Module Efficiency(%)	19.62

* STC: irradiance 1000 W/m2, AM 1.5G, and cell temperature of 25°C

THERMAL CHARACTERISTICS & OPERATING CONDITIONS

Maximum System Voltage(V)	1500
Maximum Series Fuse Rating(A)	20
Power Tolerance	0~+3%
Pmax Temperature Coefficients(W/°C)	-0.400%
Voc Temperature Coefficients(V/°C)	-0.330%
Isc Temperature Coefficients(A/°C)	+0.048%
NOCT Nominal Operating Cell Temperature(°C)	45±2
Operating and Storage Temperature(°C)	-40~+85

MECHANICAL CHARACTERISTICS

Cell Type	182*95.8Mono
No. of Cells	100(10*10)
Dimensions	1895*1076*3.5mm
Weight	7.42kg
Junction box	IP65/IP67
Output cables	4mm² cable 90cm + mc4
MaxWind Load/Snow Load	2400Pa/5400Pa