

Electrical Characteristics

电气特性

组件型号	Module Type	RT 4BW
		STC
额定功率	Maximum Power- Pmax(W)	4
开路电压	Open Circuit Voltage - Voc(V)	56
短路电流	Short- Circuit Current - Isc(A)	3.16
工作电压	Voltage at Pmax -Vmp(V)	1.33
工作电流	Current at Pmax - Imp(A)	3.00
组件效率	Module Efficiency - η (%)	24.3
功率公差	Power Tolerance(W)	0, +0.5W
最高系统电压	Maximum System Voltage(V)	500Vdc (IEC / UL)
最大额定熔断电流	Maximum Series Fuse Rating (A)	10A

标准测试条件STC: 光照强度Irradiance 1000W/m², 组件温度Cell Temperature 25°C, 大气质量AM 1.5

Mechanical Specifications

结构特性

组件尺寸	External Dimensions	200*120*20mm
重量	Weight	3.0kg
电池	Solar Cells	Mono crystalline 182x182mm (1x2pcs)
玻璃	Front/Rear Glass	2.0 mm + 2.0 mm tempered glass
边框	Frame	Aluminum
接线盒	Junction Box	IP67
输出导线	Output Cables	20cm, length can be customized
连接器	Connector	MC4 Compatible
机械载荷	Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Temperature Characteristics

温度特性

最高功率温度系数	Pmax Temperature Coefficient	-0.290%/°C
开路电压温度系数	Voc Temperature Coefficient	-0.250%/°C
短路电流温度系数	Isc Temperature Coefficient	+0.045%/°C
光伏组件工作温度	Operating Temperature	-40~+85°C
额定工作电池片温度	Nominal Operating Cell Temperature(NOCT)	45±2°C

4 Watt

RT 4BW

4瓦双玻光伏组件
182mm Cells PV Module



Packing Configuration

包装方式

组件型号	Module Type	RT4BW
组件尺寸	Module Dimensions	200*120*20mm
托盘尺寸	Pallet Dimensions	800x450x110mm
每托重量	Pallet Weight	425kg
每托数量	Pieces/Pallet	400pcs

